





Collaborative Technology Alliance (CTA)

Power & Energy (P&E)



Mr. John Hopkins
*ARL Collaborative Alliance
Manager*

Honeywell

Dr. Mukund Acharya
*Consortium Manager,
Honeywell Engines, Systems &
Services*



Power and Energy Collaborative Technology Alliance



Consortium Partners

- Honeywell (lead)
- MIT
- Clark Atlanta
- Georgia Tech
- U of Maryland
- Motorola Labs
- U of New Mexico
- Case Western Reserve U
- DuPont Fuel Cells
- NuVant Systems
- U of Puerto Rico
- Penn State Univ
- Delphi Automotive
- Tufts Univ
- U of Minnesota
- U of Pennsylvania
- U of Texas - Austin
- SAIC
- United Defense LP
- Rensselaer Polytechnic
- Rockwell Scientific

Objectives

Research and develop technologies that enable lightweight, compact power sources and highly power dense components that will significantly reduce the logistics burden, while increasing the survivability and lethality of the soldiers and systems of the highly mobile mounted

**Supporting
Transformation Goals**


Technical Areas

- **Portable, Compact Power Sources (Non-electrochemical)**
- **Fuel Cells and Fuel Reformation**
- **Hybrid Electric Propulsion and Power**





Power and Energy Collaborative Technology Alliance





DoD and Commercial Industry Requirements





Power and Energy Taxonomy



Operational Regimes

Unit of Action

Responsive Deployable
Agile and Versatile
Lethal Survivable
Sustainable

System of Systems Platforms

Ground
Manned & Unmanned
Mobile & Non-Mobile

Air
Manned &
Unmanned
Aircraft

Soldier
Future Force
Warrior, Land
Warrior

Unattended
Ground
Sensors &
Munitions

Platform Applications

Hybrid
Electric/
Propulsion

Environment
Management

Dynamic
Armor

EM, ETC,
DE
Weapons

Active
Protection

C4 ISR

Signature
Management

UGS,
Munitions,
Other

Technologies

Switches : Capacitors : Batteries :
Power

Converters : Fuel Cells : Fuel
Reformation

Thermal Management : Power Control:
Power Generation




Hybrid-Electric Combat Vehicle

Future Combat Systems



- Common power source for propulsion, EM/ETC gun, armor, and auxiliary - ability to shift power away from propulsion
- Enables improved stealth, near silent watch, and extended vehicle range
- $\geq 50\%$ increase in transient power at wheels - enhances mobility
- Increased flexibility of vehicle system integration yields up to 10% increase in useable internal volume



• Required Technology

- **Power Generation:** 2X more efficient and 2X more power dense generation
- **Energy Storage:** Energy storage at 50 kW-hr (10's MJ) and pulsed power capacitors up to 5 MW
- **Power Control and Distribution:** High power switches, control and distribution

Payoff in FY2010:

- Fuel savings up to 50%
- Reduction in armor and ammunition weight hence transport costs
- New capability for EM/ETC gun and



Cross-Service Critical Applications

Warrior Power



**Hybrid JP-8 fueled
charger/rechargeable battery system
capable of:**

- eliminating non-rechargeable batteries
- weighing 1/3 less than non-rechargeables
- extending mission time per system up to 6X



**Rechargeable batteries charged 2-3X
faster**

Energy Storage: Battery reactants with 3X increase in energy storage and 6X increase in power density. **Novel liquid electrolyte reserve batteries, TRL 6, FY07.**

Power Management design tools

**reduce power consumption 2 to 5
times**

Power Control: Efficient chargers for two hour charge time and techniques to reduce power consumption by 50% in Soldier Systems

Power Generation: Logistic fuel reformation, **Direct Methanol Fuel Cells,**

**Return on Investment
FY08 (1 Battalion, 96 Hour
Mission):**

**4400 Disposable Batteries,
\$500,000, 8800 pounds**


VERSUS

**200 Gallons JP-8,
Rechargeable Batteries,
\$400, 1600 pounds for fuel**

DMFC Fuel Cell Demo FY06






P&E CTA Focused on Three Technical Areas




Technical Area Power Levels Meet the Goals of Transformation for Soldier and Vehicular Loads

Portable Compact Power Sources




Gas Turbine & Electrostatic Generator



Electromagnetic Generator



Microfab Technology



Component Fabrication & MEMS Process Development



Portable Compact Power Sources

MEMS GAS TURBINE ENGINE



Technical Challenges:


- Improved yield from MEMS fabrication of highly complex devices
- Stable high speed rotation of silicon micro-rotors
- Silicon structure strength at high temperatures
- High performance levels from small-scale engine components

Recent Accomplishments:


- Micro-turbocharger operated at high speed (up to 480,000 rpm)
- Micro-catalytic combustor demonstrated
- Magnetic generator device designed
- Startup model for the gas




Compresso




Gas Phase
Combustio
n



Catalytic
Combustor
r




Turbine



Portable Compact Power Sources



LAMINATED MAGNETIC GENERATOR STATOR



Cutaway of a MEMS magnetic generator

- Laminations reduce eddy current losses
- Laminated microstructures were beyond the SOA
- New fabrication processes developed & demonstrated






Fabricated induction generator



Laminated Stator

Portable Compact Power Sources

3-D Profiles in Photoresist Film




- **New micromachining processes**

- Continuously variable height silicon structure demonstrated
- Grey-scale lithography makes 3D structures possible
- Gas turbines use extensive 3D geometries
- Process expands gas-turbine design space, improving performance



Catalytic Partial Sulfur Oxidation removal SOFC







Fuel Reforming: Advanced Catalysts



Technical Challenges:

- Convert Logistic Fuels and components to Hydrogen rich gas streams for SOFCs
- Develop advanced catalysts, supports and materials for catalytic partial oxidation (CPOX)
- Obtain operating parameters and that yield high conversion



Working Catalyst

Recent Accomplishments:

- Reforming of decane, hexadecane and low-sulphur diesel fuel
- Demonstrated fast lightoff of octane, iso octane, decane and hexadecane
- Determined limits of safe operation without flames or explosions




SOFEC Stack and System Level Assessment

Technical Challenges:

- Trade-offs in power density, system efficiency and fuel tolerance drive towards higher stack temperature. Metallic interconnects are a weak link in operating above 800 C.
- Reforming, Desulfurization and Stack processes interact and must be configured into a system. Assessment of the CTA and other technical progress is needed to estimate system performance and to

Recent Accomplishments


- Development of screening tests for interconnect alloy evaluation.
- Development of Hysys models for system.
- Coupled proprietary version of stack electrochemical model to system model.





Fuel Cells and Fuel Reformation

Reformed Methanol Fuel Cells


**RHFC systems,
peripherals,
integration**





**Polyphosphonic
Dopants for
Membranes**



**Reformer-ceramic
materials synthesis and
processing**



**High Temperature
Membranes**






Reformed Hydrogen Fuel Cell System

Technical Challenges:

- Identify materials that are chemically compatible for long term operation of elevated temperature fuel cell stack
- Develop low-pressure-drop 20W stack with optimal characteristics
- Develop 20W fuel processor for demonstration of principle



Recent Accomplishments:

- Completed CFD model of the Gen 1 integrated fuel processor
- Completed design and construction and currently testing Gen 3.1 fuel processor (sized for 5W system)
- Demonstrated 2W proof of principle system running for >90hrs on mini-pumps with rudimentary control scheme



Outer dimensions

ns
L = 49 mm
W = 49 mm
H = 5 mm





Reforming Catalyst in Porous Ceramic Support








Technical Challenges:

- Develop methods of wall coating of preformulated, industrial catalysts.
- Catalyst for Microchannel reformers must provide low pressure drop and high activity
- Demonstrate performance of wall coated reactor for hydrogen production
- Catalyst coating should be adherent and stable for long term use



Recent Accomplishments:

- Analysis of Heat and Mass Transfer Limitations in Packed Bed and Wall Coated Reformers
- 25 μm wall coat of catalyst demonstrated within microchannels
- Reactivity of wall coated catalyst exceeds that of packed bed




Fuel Cells and Fuel Reformation



Direct Methanol Fuel Cells



**DMFC Membranes
MEAs**







**DMFC Catalyst
Discovery
Optical catalyst
screening**



**DMFC Catalysts,
Low Methanol Crossover
Membranes**

**High throughput parallel
Screening & testing**



**DMFC anode catalyst preparation
& characterization**

DMFC System Design

Objectives

- Design and optimize a miniature 1W DMFC system.
- Model scale-up to larger systems to determine overall system size, weight, and energy density.


Challenges

- Integration and miniaturization of system components.
- Microfluidic design and processes required to maintain the structural and electrical integrity of the fuel cell system

Accomplishments


- 1W & 2W DMFC Systems designed, built and tested.
- > 1000 hour operation demonstrated for 1W prototype

Prototype 2W DMFC System





Basic Combat Hybrid Power System Architecture









Hybrid Electric Propulsion & Power







**System Integration,
Modeling
& Analysis**







**High Speed Ceramic
Turbogenerator
Robot Power Systems**

**Vehicle Integration, DC-
DC Converters**



SiC Materials & Devices

**Field Sustainment Power
Conditioning**



**SiC Device Fab, Evaluation,
Process Improvements,
Converter Design,
Turbogenerator Technology**


Hybrid Electric Propulsion & Power Vehicle Power Conversion

Technical Challenges:


- Development and fabrication of high temperature and high power density power electronics to meet aggressive space requirements on combat Hybrid Electric Vehicles (HEV) for FCS program.
- Develop and test hybrid Si/SiC oil cooled 600 amp/1200 volt IGBT module and integrate into an oil cooled inverter.

Recent Accomplishments:

- Designed new driver card for inverter to support thermal and electrical testing.
- Completed detail chip layout drawing for hybrid module.
- Completed bench test fixture design to electrically and thermally test module.
- Successfully developed backside and front side metallization and soldering processes for soldering SiC SBD to cold plate.
- Successfully developed and tested soldering and wire bonding processes to be used on the module.
- Completed fabrication and assembly of 4



Hybrid IGBT Module



Transitioned to CHPS SIL for Evaluation in Prototype FCS



Hybrid Electric Propulsion & Power High-Speed Ceramic Turbogenerator



Program Objective




Develop and validate key technology enablers

Technical Challenges:


- Compact & Fuel-efficient primary energy conversion subsystem
- High cycle temperatures
- Lubrication system limitations at high speeds
- Direct-coupled high-speed generators

Recent Accomplishments:

- Initial screening experiments demonstrated that zirconia deposited on SiCN successfully prevents the development of silica at this interface during oxidation.
- Initiated integration of start function in the generator for the gearless/oilless FPT engine configuration.
- Assessment of electrical machinery for the hybrid electrical drive system has been completed. Research on and development of disk (axial gap) type PM machines for both generating and



Free Power Turbine



Specific Weight = 0.2 lb/hp
Specific Volume = 0.04 ft³/hp



Hybrid Electric Propulsion & Power Robot Power Systems



Program Objective



Develop and demonstrate a power system that meets the mission requirements of a man-portable autonomous robot

Technical Challenges:

- 'Small' Power System Unit up to 500W with peak and continuous power for mobility and payload
- Rechargeable and Expendable power pack versions
- Short-term solution with SOA battery technology, longer-term with fuel-cell or 'new' battery technology

Recent Accomplishments:

- PacBot identified as demonstration platform.
- Power measurements on Talon and URBOT robots completed at SPAWAR. Voltage and current demands documented for conditions simulating vehicle mission components.



Robot Power System



Summary

- P&E CTA is part of the DoD and other agency programs to find solutions and efforts will be made to collaborate with other programs as appropriate
- P&E CTA website for Government and Consortium access
- Electric power demands continue to increase

Transformation for a Future Electric Force